


重荷重用ゴム車輪

重荷重用ゴム車輪(HB型)



HB200x90



ジェンゴム車輪(赤ゴム) (GHB型)



GHB250x75

耐油性・耐熱性ゴム車輪 (CRHB型)



CRHB100x50

駆動輪ゴム車(HA型)


 HA300x100 30φH7
キー8x3.3

単位(mm)

品名	車輪外径 D	許容荷重 (kg)	車輪幅 W	ボス幅 W1	軸径 d	ベアリング	リム径 D1	ボス径 D2	ベアリング 当り a	アーム数	製品重量 (kg)
HB100x50	100	150	51	55	17	6203	70	55	43	ベタ	1.3
HB100x65	100	195	64	70	17	6203	70	55	58	ベタ	1.7
HB130x50	130	200	51	54	20	6204	95	59	38	ベタ	1.9
HB130x65	130	250	64	70	20	6204	95	59	54	ベタ	2.5
HB150x50	150	225	51	57	25	6205	114	63	41	ベタ	2.1
HB150x65	150	270	64	70	25	6205	114	65	54	ベタ	3.0
HB150x75	150	345	76	82	25	6205	114	65	66	ベタ	3.6
HB150x100	150	520	102	108	30	6206	114	76	90	ベタ	6.0
HB180x50	180	270	51	57	25	6205	140	69	41	ベタ	3.0
HB180x65	180	325	64	70	25	6205	140	69	54	ベタ	3.9
HB180x75	180	350	76	82	25	6205	140	69	66	ベタ	4.3
HB200x50	200	300	51	57	25	6205	165	65	41	4	3.1
HB200x65	200	385	64	70	25	6205	165	66	54	4	3.8
HB200x75	200	450	76	82	25	6205	165	66	66	4	4.5
HB200x90	200	535	89	95	30	6206	165	78	77	4	6.1
HB230x65	230	445	64	76	25	6205	191	65	60	5	4.8
HB230x90	230	615	89	95	30	6206	191	79	77	5	5.1
HB250x65	250	480	64	76	25	6205	210	66	60	5	5.2
HB250x75	250	570	76	89	30	6206	203	81	71	5	7.0
HB250x90	250	670	89	102	30	6206	203	81	84	5	8.7
HB250x100	250	700	102	114	30	6206	203	84	96	5	11.0
HB300x65	300	580	64	82	30	6206	254	76	64	5	7.0
HB300x75	300	685	76	82	30	6206	254	77	64	5	8.1
HB300x90	300	805	89	99	30	6206	254	81	81	5	10.5
HB300x100	300	900	102	114	30	6206	254	81	96	5	12.3
HB300x130	300	1080	125	133	50	6210	254	118	113	ベタ	22.1
HB360x65	360	540	64	76	30	6206	292	78	58	5	9.7
HB360x75	360	650	76	82	30	6206	292	78	64	5	11.3
HB360x90	360	780	89	102	35	6207	280	96	82	5	13.6
HB380x90	380	840	89	102	35	6207	311	100	82	5	16.8
HB410x65	410	640	64	80	30	6206	343	80	62	5	14.1
HB410x75	410	780	76	89	35	6207	343	93	69	5	17.0
HB410x90	410	900	89	127	35	6207x6307	330	103x106	107	5	21.0
HB410x100	410	1000	102	133	35	6207x6307	330	101x109	113	5	23.1
HB410x130	410	1250	125	133	40	6208	330	113	113	5	29.8
HB460x100	460	1250	102	133	40	6208	375	113	113	5	33.1
HB460x130	460	1400	125	133	50	6210	375	123	113	5	44.9
HB510x75	510	900	76	95	35	6207	432	111	75	5	27.6
HB510x100	510	1300	102	133	50	6210	432	116	113	5	43.3
HB510x130	510	1500	127	133	50	6210	432	129	113	5	48.2
HB510x150	510	1800	150	160	50	6210	432	133	140	5	58.3

※180x50につきましては金具付の場合軸径は20φになります。

 ※駆動輪の詳細は別作カタログ
またはホームページにてご確認
下さい。